

CARD
ISSUANCE
SYSTEM

MATICA
TECHNOLOGIES

S6200GG




**ДЕПОВАЯ
ИНИЦИАТИВА**

г. Минск, л.Жуковского, 11а, офис 23
Тел./факс: + 375 17 227-01-00
Моб. MTS: + 375 29 777-71-22
E-mail: info@delinit.by
Http:// www.delinit.by



S6200GG

CARD ISSUANCE SYSTEM

Dedicated for dual-side high speed monochrome or color printing, the S6200GG pre-configured system makes it easy and affordable to print near edge-to-edge card designs, photos, logos, alphanumeric text or barcodes. The system includes two thermal printing stations which combines performance with consistent reliability of printing.

RAISING THE STANDARD OF FAST AND AFFORDABLE PRINTING

The S6200GG is the perfect solution for cost-conscious distribution of loyalty, membership, access control, employee ID, and financial cards issuance at the production volume of up to 2.000 cards per hour.

MULTIPLE CHOICE OF APPLICATIONS

Choose the card encoding options that best suits your card issuance programs. The S6200GG model can incorporate a magnetic (ISO or JIS2) stripe encoding station, a single contact or contactless smart card station or a multi smart card personalization module. The smart card personalization module is aimed at encoding up to 5 contact or 3 contactless smart cards simultaneously. A lamination module is offered as an option to add a layer of visual security and increase the lifespan of the card.

PRINTING FLEXIBILITY FOR HIGH VOLUME PRODUCTION

The system comprises two thermal printing engines for a flexible card layout creation, permitting to reach the maximum speed. The system is based on two high-speed graphic printing units including a dual-side cleaning station and a flip-over allowing card personalization in one single pass. This dual architecture makes the S6200GG one of the most competitive solution in the market.

QUALITY AND PRECISION

Matica's dual high speed S1 graphic printing engine conveys quality and precision in printing. Designed for monochrome and full-color printing it is ideally suited to print text, barcodes, logos or photos at 300 dpi resolution. The integrated flip-over station allows optimal front and rear card management and the advanced cleaning unit provides maximum quality.

SCALABLE SOLUTION

The S6200GG is a configuration that can operate in full autonomy or can upgrade into a platform with up to 5 modules. In addition, it gives you the possibility to link with an inline card mailing system for a complete card-to-envelope solution. The system is flexible for an upgrade to a S7000 high-volume issuance system for more demanding production environments.

TECHNICAL SPECIFICATIONS

Productivity

Thermal printing: up to to 2.000 cards per hour
Recommended operating time: up to 16 hours a day

Base Machine

Single card feeder 600 cards
Single card stacker 600 cards with reject card tray
Double S1 high-speed printer
Flip-over for dual side printing
Dual-side cleaning station

Options

Pro issuance kit (key locked cabinet, stack light, data encryption)
Magnetic stripe encoding
Single or multi smart card encoding station
Smart secure laminator
Graphical personalization integrity verification
Inline card mailing
Card folding and envelope insertion

Printing Specifications

Direct-to-card technology
Print method: Monochrome and color
Print area: near edge-to-edge
Printhead resolution: 300 dpi

Consumables

Black monochrome ribbon: up to 11.200 cards per roll (45 mm length per card)
5-panel YMCKO color ribbon: 1.000 cards per roll
6-panel YMCKOK color ribbon: 800 cards per roll
Half-panel YMCKO color ribbon (especially for photo): 1.400 cards per roll
*Other monochrome ribbons available on request

Software

MaticardPro Windows 7/8 based software included
Diagnostic and setup software included
Smart card SDK optional

Communication Interface

Ethernet

Other Features

In-line connection availability with the MS6000 mailer
Upgradeable firmware: via PC on Flash EPROM

Dimensions

L x W x H: 1,560 to 2,180 x 550 x 1,400 mm (61-86" x 22" x 55")

Electrical Requirements

Auto-switching internal power supply
Input 100-240 volts AC, 50-60 Hz – 600W
Interchangeable external power cord

Operating Temperature

15° / 30 °C (59° / 86 °F)