

CLM FOR PRIMACY



THE IDEAL MODULE FOR LAMINATING AND PROTECTING YOUR CARDS

Developed by Evolis, the CLM (Card Lamination Module) module is associated with the Evolis Primacy printer and is an all-in-one system for printing, encoding, and laminating all cards that need to be secure and/or protected. ID cards made using CLM can be used for up to 10 years¹ and cannot be forged.

EASY TO USE

- The CLM module is connected to the Primacy printer through infrared, forming a single system. Without replacing your printer, you can easily equip it with a lamination station.
- The films are installed intuitively and all the laminates are automatically recognized by CLM and Primacy.

PRODUCTIVITY ASSURED

- CLM and Primacy encode the cards (magnetic strip, contact or contactless smart cards), print them in D2T2, and laminate them in a single operation.
- The printing and lamination modules work in parallel and produce up to 215 printed and laminated single-sided cards or 110 double-sided cards per hour.
- The CLM module can laminate double-sided cards as standard.

WIDE CHOICE OF LAMINATES

- Evolis has a wide range of patches and laminates, with or without holograms.
- Our teams can develop personalized laminates on demand and as part of a specific project.
- All our patches and varnishes are high capacity and offer great system autonomy.

Applications :

- National ID cards
 - Driver's licenses
 - Secure access cards
 - Health cards
-



MAIN FEATURES / Full technical specifications on www.evolis.com

GENERAL FEATURES	<ul style="list-style-type: none"> • Single and double sided lamination in standard • Standard built-in card flattener
LAMINATION PERFORMANCES¹	<ul style="list-style-type: none"> • Single side: up to 215 cards/hour • Dual side: up to 110 cards/hour
CARD MANAGEMENT AND SPECIFICATIONS	<ul style="list-style-type: none"> • Feeder capacity (from Primacy): 100 cards (0.76 mm - 30 mil) • Output hopper capacity: 100 cards (0.76 mm - 30 mil) • Reject tray capacity (from Primacy): 100 cards (0.76 mm - 30 mil) • Card thickness: 0.76 mm (30 mil) • Card types: PVC cards, composite PVC cards, PET cards, polycarbonate cards, special varnished cards • Card format: ISO CR80 - ISO 7810 (53.98 mm x 85.60 mm)
INTERFACES	<ul style="list-style-type: none"> • Infrared (no cable): connection kit with Primacy included
SAFETY	<ul style="list-style-type: none"> • Support for Kensington[®] security lock
DISPLAY	<ul style="list-style-type: none"> • Printer LEDs • Graphical notifications: cleaning alerts, empty/low level ribbon, etc • LCD screen as an option (factory installed)²
EVOLIS HIGH TRUST[®] FILMS To maximize the quality and durability of printed cards, the lifespan of the print head and lamination module reliability, use Evolis High Trust [®] films.	<ul style="list-style-type: none"> • Automatic identification and setting • Color matching for easy installation • Available films: <ul style="list-style-type: none"> - Clear patch (0.5 ou 1.0 mil): 600 sides / roll - Holographic Patch (0.6 ou 1.0 mil): 600 sides / roll - Patch cuts out contact chip (0.5 ou 1 mil): 600 sides / roll - Alternate clear patch 1.0 mil (full / mag cut): 600 sides / roll² - Alternate clear patch 1.0 mil (smart cut / full): 600 sides / roll² - Alternate clear patch 1.0 mil (smart cut / mag out): 600 sides / roll² - Clear varnish: 1200 sides / roll - Holographic varnish Continuous: 1200 sides / roll - Holographic varnish Registered: 1200 sides / roll - Other films upon request • List lamination films available on www.evolis.com
OPTION	<ul style="list-style-type: none"> • Installation of a second Card Lamination Module (CLM) to laminate both sides of the card with two different films²
SOFTWARE	<ul style="list-style-type: none"> • Evolis Premium Suite[®]
CERTIFICATIONS AND STATEMENT OF COMPLIANCE	<ul style="list-style-type: none"> • CE, FCC, ICES, VCCI, CCC, KC, BIS • RoHS
SIZE AND WEIGHT	<ul style="list-style-type: none"> • CLM : <ul style="list-style-type: none"> - Size (H x W x D): 269 x 205 x 370 mm (10.59" x 8.07" x 14.56") - Weight: 6 kg (13.22 lbs) • With Primacy: <ul style="list-style-type: none"> - Size (H x W x D): 269 x 205 x 753 mm (10.59" x 8.07" x 29.64") - Weight: 10 kg (22.04 lbs)

¹ Under specific conditions / ² Available in Q4 2016

³ Warranty subject to observance of specific conditions and use of Evolis High Trust[®] films

